



REACH TRUCK

1.5T DOUBLE DEEP REACH TRUCK

UN forklifts are designed to excel in the most challenging environments with increased safety, enhanced cooling systems, reduced noise and vibration all with low maintenance. With refined performance at an affordable price, UN Forklifts reduce the total cost of ownership and provide reliable and efficient solutions to drive productivity in your operations.











MODEL		1.5T DOUBLE DEEP REACH TRUCK	
GENERAL SPECIFICATIONS			
Load Capacity	Т	1.5	
Load Capacity	Q(kg)	1500	
Load Centre	mm	500	
CHARACTERISTICS & DIMENSION			
Rated Lift Height	H3(mm)	5000	
Free Lift Height	H2(mm)	200	
Fork Size (LxWxT)	mm	920*120*35	
Mast Tilt Angle (F/R, a°/β°)	deg	3°/5°	
Length to Face of Fork	L1(mm)	2752	
Overall Width	B1(mm)	1450	
Mast Lowered Height	H1(mm)	2950	
Mast Extended Height (With Backrest)	H4(mm)	7045	
Overhead Guard Height	H5(mm)	2205	
Turning Radius	Wa(mm)	2070	
Ground Clearance	H6 (mm)	50	
Fork Carriage Reach Distance	X(mm)	920	
Front Tread	B2(mm)	1300	











MODEL		1.5T		
Wheelbase	Y(mm)	1750		
Working Aisle Width With Pallet (1200 Lengthways)	Ast(mm)	3250		
Working Aisle Width With Pallet (800 Lengthways)	Ast(mm)	3325		
Working Aisle Width With Pallet(Empty)	Ast(mm)	3055		
TYRE				
Front Tyrex2 (Polyurethane)	mm	125x75x4		
Rear Tyrex1 (Polyurethane)	mm	343x135		
PERFORMANCE				
Travel Speed (Full Load)	km/h	9.0		
Travel Speed (No Load)	km/h	9.5		
Lifting Speed (Full Load)	mm/sec	240		
Lifting Speed (No Load)	mm/s	360		
WEIGHT				
Total Weight (Include Battery Box)	kg	4060		
Battery Weight	kg	756		
DRIVE				
Diver Motor	Kw	6		
Pump Motor	Kw	11		
Battery (Standard)	V/Ah	48/420		
Steering System		Electronic		
Service Brake		Electromagnetic		
Controller Type		AC		
Controller Manufacturer		ZAPI		
Operating Pressure	Мра	16		
EXTRAS INCLUDED				
Side-Shift	•	•		
Fork postioner	•	•		
Solid Non-Marking Tyres	•	•		





